

Company Name:

Surveyor:

Customer Ref:..... **Date:**.....

Location in the house:.....

W: _____ x **H:** _____

Quantity the same: (only 1 style per page)

Concealed Trickle Vents? 1. No 2. Yes,
Airflow required? _____ mm² **QTY** required? _____

Colour of furniture? POLISHED CHROME / SATIN CHROME /
 POLISHED BRASS / ANTIQUE PEWTER / ANTIQUE BLACK

Child locks 100mm Restrictor (only if no inside horns): YES or NO

Timber types
Frames & Cill:
 1. SW: Pine (Redwood, any finish)
 2. HW: Sapele/Meranti (Smooth finish only)
 3. HW: Oak (Stain, Natural finish only)
 4. SW: Pine (Redwood) Frame + HW Cills (Sapele)

Colour and finish inside and outside:
 1. Fully finished Satin White - Natural / Smooth / Grainy
 2. Satin RAL, N°: _____ - Natural / Smooth / Grainy
 3. Satin Stained, N°: _____ - Natural only

Horns (decorative, outside only):
 1. Standard as drawn here
 2. Custom - draw design in empty field
 3. None

Architrave: (standard OG, painted to match window)
 1. YES - 70mm only // a. Top & Sides OR b. All 4 sides?
 2. NO

Architrave to wall fillers // Top & Sides OR All 4 sides?
 1. YES, size? Write W x H here →
 2. NO

Internal window board:
 1. YES // Factory bull nosed ends? Yes or No
 • Depth: 50 / 100 / 150 / 200 mm
 ▪ Length (inc bull nosed ends) _____ mm.
 2. NO

Cill projection? (From outside face of 155mm frame)
 1. YES, Frame Depth + _____ mm = _____ mm overall,
 Protruded Cill Length each side, to wrap around wall:
 None or + 50mm or + 100mm or + 200mm each side?
 2. NONE

Arched Top Options:
 1. None
 2. Arched Tops (Arched Frame & Top Sash)
 3. Arched Tops (Arched Top Sash Timber Corners,
 Square Frame Arched Outside Under Brick Work)
 4. Swept Heads (Arch in Sash Only, Frames All Square)

Std Glass (4-16-4 = 24mm overall): Glass by ATW or Customer?
TOP: Clear Std or Obscure type? _____ (Circle) / Safety?
BOTTOM: Clear Std or Obscure type? _____ (Circle) / Safety?

Inside Glazing System: (Butyl/Silicone to match frame)
 1. Black Warm Edge Spacer bar
 2. White Warm Edge Spacer bar

Glazing (Georgian) bar: YES or NO (select type and draw
 where required onto each sash as dotted line, e.g.- - - - -)
 • 22 mm astragal (on top of glass)
 • 45 mm through glass with separate glass units.

Fire Escape: YES / NO (min clear bottom area dimensions to be
 450mmx755mm>0.34m²)

